

MIRA AZORA

Part Number: 9.8kW Frosted Glass: 1.1634.011

GREAT SPORT
TECHNOLOGY
WITH A
MINIMALIST
TWIST



HIGH PERFORMANCE

Opti-flo™ delivers up to 50% more flow in summer

TEMPERATURE CONTROL

Thermostatic temperature stability

EASY TO FIT

Retrofits onto inlets of most Mira electric showers

EASY TO SERVICE

Easy filter access

FOR YOUR CUSTOMER

Separate controls for power and temperature

Sensi-flo™ helps prevent scalding

Clearscale™ & Dual Element™ – reduces limescale by up to 50%

Phased shutdown flushes hot water from the tank making it safe for the next user

4 spray 11cm showerhead with rub clean nozzles

TECH DETAILS

TEMPERATURE CONTROL

Control type: Thermostatic (SMA)

INSTALLATION

Power options: 9.8kW 240v AC (9.0kW 230V AC)

Supply voltage: 230v \pm 10%

Supply rating: 45 amp (9.8kW)

Terminal block connections: maximum 16mm²

Water entry points: Left (rising, falling & rear)

Cable entry points: Left (rising, falling & rear)

Inlet connections: Brass inlet connector.
15mm compression fitting

Outlet connections: ½" BSP Male

SUPPLY CONDITIONS

Minimum maintained pressure: 0.7 bar (7 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

PERFORMANCE

Temperature stability: \pm 2°C

SAFETY FEATURES

Phased shutdown: Yes

Factory set to safe max temp: Factory set at 48°C

Sensi-flo™: Yes

ACCESSORIES

Wide range of accessories available at
www.mirashowers-store.co.uk

TECH DRAWINGS

